



QualityBox PC EK358 | Compact K1

Internal dimensions: 400 x 400 mm

Outer dimensions: 540 x 540 mm

Compact manhole with cast-iron cover:			Clearance height: 580 mm
Test classes according to DIN EN 124	B 125²	D 400³	
Cover	29.0 kg	29.0 kg	
Hot-dip galvanised steel frame	17.0 kg	17.0 kg	
Frame*	26.0 kg	26.0 kg	
Base plate	2.0 kg	2.0 kg	
Total weight of compact manhole	74.0 kg	74.0 kg	
Overall height of compact manhole	680 mm	680 mm	

Compact manhole with concrete-lined steel cover:			Clearance height: 630 mm
Test classes according to DIN EN 124	B 125²	D 400³	
Cover	49.0 kg	49.0 kg	
Hot-dip galvanised steel frame	23.0 kg	23.0 kg	
Frame*	26.0 kg	26.0 kg	
Base plate	2.0 kg	2.0 kg	
Total weight of compact manhole	100.0 kg	100.0 kg	
Overall height of compact manhole	735 mm	735 mm	

Compact manhole with paveable steel cover: (paveable height 45 mm)			Clearance height: 630 mm
Test classes according to DIN EN 124	B 125²	D 400³	
Cover (without paving)	55.0 kg	55.0 kg	
Hot-dip galvanised steel frame	27.0 kg	27.0 kg	
Frame*	26.0 kg	26.0 kg	
Base plate	2.0 kg	2.0 kg	
Total weight of compact manhole	110.0 kg	110.0 kg	
Overall height of compact manhole	780 mm	780 mm	

* **Pipe entries**, each front side: 4 x 110 mm diameter

* **Pipe entries**, each long side: 4 x 110 mm diameter



QualityBox PC EK358 | Compact K1 Order numbers

Internal dimensions: 400 x 400 mm

Outer dimensions: 540 x 540 mm

Manhole with cast-iron cover, lockable ⁴	Order number
Compact manhole B 125, not locked, locks retrofittable	06 358 1180
Compact manhole D 400, hex locking mechanism	06 358 1257
Compact manhole D 400, hex socket locking mechanism	06 358 1258
Compact manhole D 400, LIC-lock locking mechanism	06 358 1259
Compact manhole D 400, COLT/TELENET locking mechanism	06 358 1260
Accessories for cast-iron cover, lockable	
1 x hex locking mechanism	50 000 6020
1 x hex socket locking mechanism	50 000 6040
1 x LIC-lock locking mechanism	50 000 6060
1 x COLT/TELENET locking mechanism	50 000 6080
Sealing plug for locking mechanism, black	70 046 0716
Cast-iron cover B 125, 1-piece	70 033 9382E
Cast-iron cover D 400, 1-piece	70 033 9483E
Steel frame	70 034 5280E
Manhole with concrete-lined steel cover, lockable ⁴	
Compact manhole B 125, not locked, locks retrofittable	06 358 1216
Compact manhole D 400, hex locking mechanism	06 358 1261
Compact manhole D 400, hex socket locking mechanism	06 358 1262
Compact manhole D 400, LIC-lock locking mechanism	06 358 1263
Compact manhole D 400, COLT/TELENET locking mechanism	06 358 1264
Accessories for concrete-lined steel cover, lockable	
2 x hex locking mechanism	50 000 6100
2 x hex socket locking mechanism	50 000 7100
2 x LIC-lock locking mechanisms	50 000 8100
2 x COLT/TELENET locking mechanism	50 000 9100
Sealing plug for locking mechanism, black	70 046 0716
Concrete-lined steel cover, B 125, 1-piece	70 040 6385E
Concrete-lined steel cover, D 400, 1-piece	70 040 6380E
Steel frame	70 039 6680E
Manhole with paveable steel cover, lockable ⁴	
Compact manhole B 125, not locked, locks retrofittable	06 358 1265
Compact manhole D 400, not locked, locks retrofittable	06 358 1266
Accessories for paveable steel cover, lockable	
2 x hex locking mechanism	50 000 6150
2 x hex socket locking mechanism	50 000 6160
2 x LIC-lock locking mechanisms	50 000 6170
2 x COLT/TELENET locking mechanism	50 000 6180
Sealing plug for locking mechanism, black	70 046 0716
Paveable steel cover, D 400, 1-piece	70 088 1700E
Steel frame	70 088 1720E



QualityBox PC EK358 | Compact K2

Internal dimensions: 400 x 400 mm

Outer dimensions: 540 x 540 mm

Compact manhole with cast-iron cover:			Clearance height: 580 mm
Test classes according to DIN EN 124	B 125²	D 400³	
Cover	29.0 kg	29.0 kg	
Hot-dip galvanised steel frame	17.0 kg	17.0 kg	
Frame*	26.5 kg	26.5 kg	
Base plate	2.0 kg	2.0 kg	
Total weight of compact manhole	74.5 kg	74.5 kg	
Overall height of compact manhole	680 mm	680 mm	

Compact manhole with concrete-lined steel cover:			Clearance height: 630 mm
Test classes according to DIN EN 124	B 125²	D 400³	
Cover	49.0 kg	49.0 kg	
Hot-dip galvanised steel frame	23.0 kg	23.0 kg	
Frame*	26.5 kg	26.5 kg	
Base plate	2.0 kg	2.0 kg	
Total weight of compact manhole	100.5 kg	100.5 kg	
Overall height of compact manhole	735 mm	735 mm	

Compact manhole with paveable steel cover: (paveable height 45 mm)			Clearance height: 630 mm
Test classes according to DIN EN 124	B 125²	D 400³	
Cover (without paving)	55.0 kg	55.0 kg	
Hot-dip galvanised steel frame	27.0 kg	27.0 kg	
Frame*	26.5 kg	26.5 kg	
Base plate	2.0 kg	2.0 kg	
Total weight of compact manhole	110.5 kg	110.5 kg	
Overall height of compact manhole	780 mm	780 mm	

* **Pipe entries**, each front side: 2 x 160 mm diameter

* **Pipe entries**, each long side: 2 x 160 mm diameter



QualityBox PC EK358 | Compact K2 Order numbers

Internal dimensions: 400 x 400 mm

Outer dimensions: 540 x 540 mm

Manhole with concrete-lined steel cover, lockable ⁴	Order number
Compact manhole B 125, not locked, locks retrofittable	06 358 1267
Compact manhole D 400, hex locking mechanism	06 358 1268
Compact manhole D 400, hex socket locking mechanism	06 358 1269
Compact manhole D 400, LIC-lock locking mechanism	06 358 1270
Compact manhole D 400, COLT/TELENET locking mechanism	06 358 1271
Accessories for cast-iron cover, lockable	
1 x hex locking mechanism	50 000 6020
1 x hex socket locking mechanism	50 000 6040
1 x LIC-lock locking mechanism	50 000 6060
1 x COLT/TELENET locking mechanism	50 000 6080
Sealing plug for locking mechanism, black	70 046 0716
Cast-iron cover B 125, 1-piece	70 033 9382E
Cast-iron cover D 400, 1-piece	70 033 9483E
Steel frame	70 034 5280E
Manhole with concrete-lined steel cover, lockable ⁴	
Compact manhole B 125, not locked, locks retrofittable	06 358 1246
Compact manhole D 400, hex locking mechanism	06 358 1273
Compact manhole D 400, hex socket locking mechanism	06 358 1274
Compact manhole D 400, LIC-lock locking mechanism	06 358 1275
Compact manhole D 400, COLT/TELENET locking mechanism	06 358 1276
Accessories for concrete-lined steel cover, lockable	
2 x hex locking mechanism	50 000 6100
2 x hex socket locking mechanism	50 000 7100
2 x LIC-lock locking mechanisms	50 000 8100
2 x COLT/TELENET locking mechanism	50 000 9100
Sealing plug for locking mechanism, black	70 046 0716
Concrete-lined steel cover, B 125, 1-piece	70 040 6385E
Concrete-lined steel cover, D 400, 1-piece	70 040 6380E
Steel frame	70 039 6680E
Manhole with paveable steel cover, lockable ⁴	
Compact manhole B 125, not locked, locks retrofittable	06 358 1279
Compact manhole D 400, not locked, locks retrofittable	06 358 1280
Accessories for paveable steel cover, lockable	
2 x hex locking mechanism	50 000 6150
2 x hex socket locking mechanism	50 000 6160
2 x LIC-lock locking mechanisms	50 000 6170
2 x COLT/TELENET locking mechanism	50 000 6180
Sealing plug for locking mechanism, black	70 046 0716
Paveable steel cover, D 400, 1-piece	70 088 2300E
Steel frame	70 088 2320E