



QualityBox PC EK388 | Compact K1


Internal dimensions: 650 x 650 mm

Outer dimensions: 800 x 800 mm

Compact manhole with concrete-lined steel cover:

Clearance height: 630 mm


Test classes according to DIN EN 124	B 125 ²	D 400 ³
Cover	125.0 kg	125.0 kg
Hot-dip galvanised steel frame	37.0 kg	37.0 kg
Frame*	32.0 kg	32.0 kg
Base plate	4.5 kg	4.5 kg
Total weight of compact manhole	198.5 kg	198.5 kg
Overall height of compact manhole	735 mm	735 mm



Compact manhole with paveable steel cover: (paveable height 45 mm)

Clearance height: 630 mm

Test classes according to DIN EN 124	B 125 ²	D 400 ³
Cover (without paving)	132.0 kg	132.0 kg
Hot-dip galvanised steel frame	42.5 kg	42.5 kg
Frame*	32.0 kg	32.0 kg
Base plate	4.5 kg	4.5 kg
Total weight of compact manhole	211.0 kg	211.0 kg
Overall height of compact manhole	780 mm	780 mm



* Pipe entries, each front side: 8 x 110 mm diameter

* Pipe entries, each long side: 8 x 110 mm diameter



QualityBox PC EK388 | Compact K1 Order numbers

Internal dimensions: 650 x 650 mm

Outer dimensions: 800 x 800 mm

Manhole with concrete-lined steel cover, lockable ⁴	Order number
Compact manhole B 125, not locked, locks retrofittable	06 388 1104
Compact manhole D 400, hex locking mechanism	06 388 1062
Compact manhole D 400, hex socket locking mechanism	06 388 1193
Compact manhole D 400, LIC-lock locking mechanism	06 388 1194
Compact manhole D 400, COLT/TELENET locking mechanism	06 388 1195
Accessories for concrete-lined steel cover, lockable	
2 x hex locking mechanism	50 000 6100
2 x hex socket locking mechanism	50 000 7100E
2 x LIC-lock locking mechanisms	50 000 8100
2 x COLT/TELENET locking mechanism	50 000 9100
Sealing plug for locking mechanism, black	70 046 0716
Concrete-lined steel cover, B 125, 1-piece	70 040 4585E
Concrete-lined steel cover, D 400, 1-piece	70 040 4580E
Steel frame	70 039 7580E
Manhole with paveable steel cover, lockable ⁴	
Compact manhole B 125, not locked, locks retrofittable	06 388 1197
Compact manhole D 400, not locked, locks retrofittable	06 388 1198
Accessories for paveable steel cover, lockable	
2 x hex locking mechanism	50 000 6150
2 x hex socket locking mechanism	50 000 6160
2 x LIC-lock locking mechanisms	50 000 6170
2 x COLT/TELENET locking mechanism	50 000 6180
Sealing plug for locking mechanism, black	70 046 0716
Paveable steel cover, D 400, 1-piece	70 088 2500E
Steel frame	70 088 2520E



QualityBox PC EK388 | Compact K2


Internal dimensions: 650 x 650 mm

Outer dimensions: 800 x 800 mm

Compact manhole with concrete-lined steel cover:

Clearance height: 630 mm


Test classes according to DIN EN 124	B 125 ²	D 400 ³
Cover	125.0 kg	125.0 kg
Hot-dip galvanised steel frame	37.0 kg	37.0 kg
Frame*	31.5 kg	31.5 kg
Base plate	4.5 kg	4.5 kg
Total weight of compact manhole	198.0 kg	198.0 kg
Overall height of compact manhole	735 mm	735 mm



Compact manhole with paveable steel cover: (paveable height 45 mm)

Clearance height: 630 mm

Test classes according to DIN EN 124	B 125 ²	D 400 ³
Cover (without paving)	132.0 kg	132.0 kg
Hot-dip galvanised steel frame	42.5 kg	42.5 kg
Frame*	31.5 kg	31.5 kg
Base plate	4.5 kg	4.5 kg
Total weight of compact manhole	210.5 kg	210.5 kg
Overall height of compact manhole	780 mm	780 mm



* Pipe entries, each front side: 2 x Ø 160 mm / 4 x Ø 110 mm

* Pipe entries, each long side: 2 x Ø 160 mm / 4 x Ø 110 mm



QualityBox PC EK388 | Compact K2 Order numbers

Internal dimensions: 650 x 650 mm

Outer dimensions: 800 x 800 mm

Manhole with concrete-lined steel cover, lockable ⁴	Order number
Compact manhole B 125, not locked, locks retrofittable	06 388 1200
Compact manhole D 400, hex locking mechanism	06 388 1201
Compact manhole D 400, hex socket locking mechanism	06 388 1202
Compact manhole D 400, LIC-lock locking mechanism	06 388 1203
Compact manhole D 400, COLT/TELENET locking mechanism	06 388 1204
Accessories for concrete-lined steel cover, lockable	
2 x hex locking mechanism	50 000 6100
2 x hex socket locking mechanism	50 000 7100
2 x LIC-lock locking mechanisms	50 000 8100
2 x COLT/TELENET locking mechanism	50 000 9100
Sealing plug for locking mechanism, black	70 046 0716
Concrete-lined steel cover, B 125, 1-piece	70 040 4585E
Concrete-lined steel cover, D 400, 1-piece	70 040 4580E
Steel frame	70 039 7580E
Manhole with paveable steel cover, lockable ⁴	
Compact manhole B 125, not locked, locks retrofittable	06 388 1207
Compact manhole D 400, not locked, locks retrofittable	06 388 1208
Accessories for paveable steel cover, lockable	
2 x hex locking mechanism	50 000 6150
2 x hex socket locking mechanism	50 000 6160
2 x LIC-lock locking mechanisms	50 000 6170
2 x COLT/TELENET locking mechanism	50 000 6180
Sealing plug for locking mechanism, black	70 046 0716
Paveable steel cover, D 400, 1-piece	70 088 2500E
Steel frame	70 088 2520E



QualityBox PC EK388 | Compact K3


Internal dimensions: 650 x 650 mm

Outer dimensions: 800 x 800 mm

Compact manhole with concrete-lined steel cover:

Clearance height: 630 mm


Test classes according to DIN EN 124	B 125 ²	D 400 ³
Cover	125.0 kg	125.0 kg
Hot-dip galvanised steel frame	37.0 kg	37.0 kg
Frame*	30.0 kg	30.0 kg
Base plate	4.5 kg	4.5 kg
Total weight of compact manhole	196.5 kg	196.5 kg
Overall height of compact manhole	735 mm	735 mm



Compact manhole with paveable steel cover: (paveable height 45 mm)

Clearance height: 630 mm

Test classes according to DIN EN 124	B 125 ²	D 400 ³
Cover (without paving)	132.0 kg	132.0 kg
Hot-dip galvanised steel frame	42.5 kg	42.5 kg
Frame*	30.0 kg	30.0 kg
Base plate	4.5 kg	4.5 kg
Total weight of compact manhole	209.0 kg	209.0 kg
Overall height of compact manhole	780 mm	780 mm



* Pipe entries, each front side: 4 x Ø 110 mm / 2 x rectangular

* Pipe entries, each long side: 8 x 110 mm diameter



QualityBox PC EK388 | Compact K3 Order numbers

Internal dimensions: 650 x 650 mm

Outer dimensions: 800 x 800 mm

Manhole with concrete-lined steel cover, lockable ⁴	Order number
Compact manhole B 125, not locked, locks retrofittable	06 388 1184
Compact manhole D 400, hex locking mechanism	06 388 1185
Compact manhole D 400, hex socket locking mechanism	06 388 1186
Compact manhole D 400, LIC-lock locking mechanism	06 388 1187
Compact manhole D 400, COLT/TELENET locking mechanism	06 388 1188
Accessories for concrete-lined steel cover, lockable	
2 x hex locking mechanism	50 000 6100
2 x hex socket locking mechanism	50 000 7100
2 x LIC-lock locking mechanisms	50 000 8100
2 x COLT/TELENET locking mechanism	50 000 9100
Sealing plug for locking mechanism, black	70 046 0716
Concrete-lined steel cover, B 125, 1-piece	70 040 4585E
Concrete-lined steel cover, D 400, 1-piece	70 040 4580E
Steel frame	70 039 7580E
Manhole with paveable steel cover, lockable ⁴	
Compact manhole B 125, not locked, locks retrofittable	06 388 1191
Compact manhole D 400, not locked, locks retrofittable	06 388 1192
Accessories for paveable steel cover, lockable	
2 x hex locking mechanism	50 000 6150
2 x hex socket locking mechanism	50 000 6160
2 x LIC-lock locking mechanisms	50 000 6170
2 x COLT/TELENET locking mechanism	50 000 6180
Sealing plug for locking mechanism, black	70 046 0716
Paveable steel cover, D 400, 1-piece	70 088 2500E
Steel frame	70 088 2520E



QualityBox PC EK388 | Compact K4

Internal dimensions: 650 x 650 mm

Outer dimensions: 800 x 800 mm

Compact manhole with concrete-lined steel cover:			Clearance height: 630 mm
Test classes according to DIN EN 124	B 125²	D 400³	
Cover	125.0 kg	125.0 kg	
Hot-dip galvanised steel frame	37.0 kg	37.0 kg	
Frame*	28.0 kg	28.0 kg	
Base plate	4.5 kg	4.5 kg	
Total weight of compact manhole	194.5 kg	194.5 kg	
Overall height of compact manhole	735 mm	735 mm	

Compact manhole with paveable steel cover: (paveable height 45 mm)			Clearance height: 630 mm
Test classes according to DIN EN 124	B 125²	D 400³	
Cover (without paving)	132.0 kg	132.0 kg	
Hot-dip galvanised steel frame	42.5 kg	42.5 kg	
Frame*	28.0 kg	28.0 kg	
Base plate	4.5 kg	4.5 kg	
Total weight of compact manhole	207.0 kg	207.0 kg	
Overall height of compact manhole	780 mm	780 mm	

* **Pipe entries**, each front side: 4 x Ø 110 mm / 2 x rectangular

* **Pipe entries**, each long side: 4 x Ø 110 mm / 2 x rectangular



QualityBox PC EK388 | Compact K4 Order numbers

Internal dimensions: 650 x 650 mm

Outer dimensions: 800 x 800 mm

Manhole with concrete-lined steel cover, lockable ⁴	Order number
Compact manhole B 125, not locked, locks retrofittable	06 388 1175
Compact manhole D 400, hex locking mechanism	06 388 1176
Compact manhole D 400, hex socket locking mechanism	06 388 1177
Compact manhole D 400, LIC-lock locking mechanism	06 388 1178
Compact manhole D 400, COLT/TELENET locking mechanism	06 388 1179
Accessories for concrete-lined steel cover, lockable	
2 x hex locking mechanism	50 000 6100
2 x hex socket locking mechanism	50 000 7100
2 x LIC-lock locking mechanisms	50 000 8100
2 x COLT/TELENET locking mechanism	50 000 9100
Sealing plug for locking mechanism, black	70 046 0716
Concrete-lined steel cover, B 125, 1-piece	70 040 4585E
Concrete-lined steel cover, D 400, 1-piece	70 040 4580E
Steel frame	70 039 7580E
Manhole with paveable steel cover, lockable ⁴	
Order number	
Compact manhole B 125, not locked, locks retrofittable	06 388 1182
Compact manhole D 400, not locked, locks retrofittable	06 388 1183
Accessories for paveable steel cover, lockable	
2 x hex locking mechanism	50 000 6150
2 x hex socket locking mechanism	50 000 6160
2 x LIC-lock locking mechanisms	50 000 6170
2 x COLT/TELENET locking mechanism	50 000 6180
Sealing plug for locking mechanism, black	70 046 0716
Paveable steel cover, D 400, 1-piece	70 088 2500E
Steel frame	70 088 2520E