



## QualityBox PC EK708 Basic kits

Internal dimensions: 800 x 1600 mm

Outer dimensions: 960 x 1760 mm

Basic kit with <b>cast-iron</b> cover:		Clearance height: 100 mm
Test classes according to DIN EN 124	<b>B 125<sup>2</sup></b>	
Complete cover	250.0 kg	
Single cover	62.5 kg	
Hot-dip galvanised steel frame	38.0 kg	
Top frame (standard height)	37.5 kg	
Base plate	12.5 kg	
<b>Total weight of basic kit</b>	<b>338.0 kg</b>	
<b>Overall height of basic kit</b>	<b>240 mm</b>	

Basic kit with <b>concrete-lined steel</b> cover:			Clearance height: 190 mm
Test classes according to DIN EN 124	<b>B 125<sup>2</sup></b>	<b>D 400<sup>3</sup></b>	
Complete cover	381.0 kg	381.0 kg	
Single cover	127.0 kg	127.0 kg	
Hot-dip galvanised steel frame	59.0 kg	59.0 kg	
Top frame (standard height)	37.5 kg	37.5 kg	
Base plate	12.5 kg	12.5 kg	
<b>Total weight of basic kit</b>	<b>490.0 kg</b>	<b>490.0 kg</b>	
<b>Overall height of basic kit</b>	<b>310 mm</b>	<b>310 mm</b>	

Basic kit with <b>paveable steel</b> cover: (paveable height 45 mm)			Clearance height: 190 mm
Test classes according to DIN EN 124	<b>B 125<sup>2</sup></b>	<b>D 400<sup>3</sup></b>	
Complete cover (without paving)	400.0 kg	400.0 kg	
Single cover (without paving)	133.0 kg	133.0 kg	
Hot-dip galvanised steel frame	79.0 kg	79.0 kg	
Top frame (standard height)	37.5 kg	37.5 kg	
Base plate	12.5 kg	12.5 kg	
<b>Total weight of basic kit</b>	<b>529.0 kg</b>	<b>529.0 kg</b>	
<b>Overall height of basic kit</b>	<b>355 mm</b>	<b>355 mm</b>	

Basic kit with <b>chequered stud plate</b> cover:		Clearance height: 120 mm
Test classes according to DIN EN 124	<b>A 15<sup>1</sup></b>	
Complete cover	114.0 kg	
Single cover	38.0 kg	
Hot-dip galvanised steel frame	33.5 kg	
Top frame (standard height)	35.0 kg	
Base plate	11.0 kg	
<b>Total weight of basic kit</b>	<b>193.5 kg</b>	
<b>Overall height of basic kit</b>	<b>240 mm</b>	



## QualityBox PC EK708 Frame


Internal dimensions: 800 x 1600 mm  
Outer dimensions: 960 x 1760 mm




**Frame 70 mm**  
Art. no.: 06 708 0058E  
6 x Ø 50  
Weight: 20.5 kg




**Frame 70 mm  
overbuild**  
Art. no.: 06 708 0358E  
4 x overbuild / 2 x Ø 50  
Weight: 20.5 kg




**Frame 220 mm**  
Art. no.: 06 708 0052E  
5 x Ø 110  
8 x Ø 110  
Weight: 53.0 kg



**Frame 220 mm**  
Art. no.: 06 708 0061E  
2 x rectangular / 1 x Ø 110  
8 x Ø 110  
Weight: 49.0 kg



**Frame 220 mm**  
Art. no.: 06 708 0085E  
5 x Ø 110  
4 x rectangular  
Weight: 39.0 kg



**Frame 220 mm**  
Art. no.: 06 708 0086E  
2 x rectangular / 1 x Ø 110  
4 x rectangular  
Weight: 46.0 kg



## QualityBox PC EK708 Order numbers

Internal dimensions: 800 x 1600 mm

Outer dimensions: 960 x 1760 mm

<b>Manhole with cast-iron cover, screwed down</b>	<b>Order number</b>
Basic kit B 125, not screwed, screw connection retrofittable	06 708 1075
<b>Accessories for cast-iron cover, screwed down</b>	
12 x hex screw connection	50 000 5600
12 x hex socket screw connection	50 000 5610
12 x LIC-lock screw connections	50 000 5700
12 x COLT/TELENET screw connection	50 000 5710
Sealing plug for screw connection, black	70 043 0300
Cast-iron cover B 125, 4-piece, with joint bars	70 044 6700E
Steel frame	70 044 7300E
<b>Manhole with concrete-lined steel cover, lockable <sup>4</sup></b>	<b>Order number</b>
Basic kit B 125, not locked, locks retrofittable	06 708 1003
Basic kit D 400, hex locking mechanism	06 708 1066
Basic kit D 400, hex socket locking mechanism	06 708 1067
Basic kit D 400, LIC-lock locking mechanism	06 708 1068
Basic kit D 400, COLT/TELENET locking mechanism	06 708 1069
<b>Accessories for concrete-lined steel cover, lockable</b>	
6 x hex locking mechanism	50 000 6500
6 x hex socket locking mechanism	50 000 7500
6 x LIC-lock locking mechanisms	50 000 8500
6 x COLT/TELENET locking mechanism	50 000 9500
Sealing plug for locking mechanism, black	70 046 0716
Concrete-lined steel cover, B 125, 3-piece	70 046 0275E
Concrete-lined steel cover, D 400, 3-piece	70 046 0270E
Steel frame	70 042 0680E
<b>Manhole with paveable steel cover, lockable <sup>4</sup></b>	<b>Order number</b>
Basic kit B 125, not locked, locks retrofittable	06 708 1004
Basic kit D 400, unlocked, locks retrofittable	06 708 1077
<b>Accessories for paveable steel cover, lockable</b>	
6 x hex locking mechanism	50 000 6500
6 x hex socket locking mechanism	50 000 7500
6 x LIC-lock locking mechanisms	50 000 8500
6 x COLT/TELENET locking mechanism	50 000 9500
Sealing plug for locking mechanism, black	70 046 0716
Paveable steel cover, D 400, 3-piece	70 088 2900E
Steel frame	70 088 2920E



## QualityBox PC EK708 Order numbers

Internal dimensions: 800 x 1600 mm

Outer dimensions: 960 x 1760 mm

<b>Manhole with chequered stud plate cover, screwed down</b>	<b>Order number</b>
Basic kit A 15, hex screw connection	06 708 1489
Basic kit A 15, hex socket screw connection	06 708 1490
Basic kit A 15, LIC-lock screw connection	06 708 1491
Basic kit A 15, COLT/TELENET screw connection	06 708 1492
<b>Accessories for chequered stud plate cover, screwed down</b>	
6 x hex screw connection	50 000 2460
6 x hex socket screw connection	50 000 2470
6 x LIC-lock screw connections	50 000 2480
6 x COLT/TELENET screw connection	50 000 2490
Chequered stud plate cover, A 15, 3-piece	06 708 0097E
Steel frame	70 065 0700E
<b>For all basic kits</b>	<b>Order number</b>
Top frame, height 140 mm	06 708 0082E
Base plate, height 5 mm	06 708 0054E